

25 **06** **06** - **WC1** - **1** - **S021** - **M04** - **C175** - **L01** - **E00** - **B00**

Table Series

Carriage Length

06 - 6 inches **12** - 12 inches

Travel Length (see pages I-6 & I-8)

06 - 6 to 56 inches

Waycovers

WC0 - with no waycovers **WC1** - with waycovers

Carriage Inserts (see pages I-7 & I-9)

1 - English mount **2** - Metric mount

Screw Options (see pages I-18 to I-21)

Rolled ball screws

S021 - 1.000 x .250 NPL
S022 - 1.000 x .250 PL
S023 - 1.000 x .250 NPL(T)
S024 - 1.000 x .250 PL(T)
S025 - 1.000 x .500 NPL
S026 - 1.000 x .500 PL
S027 - 1.000 x .500 NPL(T)
S028 - 1.000 x .500 PL(T)
S029 - 1.000 x 1.000 NPL
S030 - 1.000 x 1.000 PL
S031 - 1.000 x 1.000 NPL(T)
S032 - 1.000 x 1.000 PL(T)

Precision ball screws

S130 - 1.000 x .200 NPL
S131 - 1.000 x .200 PL
S132 - 25 x 10 NPL
S133 - 25 x 10 PL
S134 - 25 x 25 NPL
S135 - 25 x 25 PL

Ground ball screws

S218 - 1.000 x .200 PL
S219 - 1.000 x .500 PL
S220 - 25 x 25 PL

Rolled acme screws

S310 - 1.000 x .100 NPL
S311 - 1.000 x .100 PL
S312 - 1.000 x .200 NPL
S313 - 1.000 x .200 PL

S999 - other

Motor Mount (see pages I-7 & I-9, I-24 to I-25)

M00 - none **M04** - NEMA 34 mount (E) **M10** - NEMA 42 mount (E)
M05 - NEMA 34 mount (M) **M11** - NEMA 42 mount (M)
M08 - NEMA 34 (RH) wrap **M12** - NEMA 42 (RH) wrap
M09 - NEMA 34 (LH) wrap **M13** - NEMA 42 (LH) wrap

Coupling Options (see pages I-22 to I-23)

C000 - none **C064 to C068** - C125 **C175 to C182** - H131 **C455 to C462** - G126
C999 - other **C091 to C097** - C150 **C212 to C222** - H163 **C492 to C502** - G158

Limit & Home Switches (see pages I-15 to I-17)

L00 - no switches Mechanical Reed Hall Prox (NPN) Prox (PNP)
L99 - other EOT & home switches **L01** **L04** **L07** **L10** **L13**
EOT switches only **L02** **L05** **L08** **L11** **L14**
home switch only **L03** **L06** **L09** **L12** **L15**

Encoder Options (see page I-27)

E00 - none **E02** - rotary (1000 lines/rev) **E10** - linear (2500 lines/inch) **E99** - other
E01 - rotary (500 lines/rev) **E03** - rotary (1270 lines/rev) **E11** - linear (125 lines/mm)

Power-off Brakes (see page I-26)

B00 - none **B05** - 24 VDC **B06** - 90 VDC **B99** - other

(E) - English Interface (NPL) - Non Preloaded
(LH) - Left Hand (PL) - Preloaded
(M) - Metric Interface (RH) - Right Hand
(T) - Turcite Nut