

	553	10	012	-	D1	-	M04	-	C293	-	L04	-	E00	-	B00
Table Series															
553 - 553 carriage															
554 - 554 carriage															
555 - 555 carriage															
Carriage Length															
10 - 10 inches															
Travel Length (see page K-6)															
012 - 12 to 360 inches															
Drive Shaft (see page K-7)															
D1 - Right Hand single shaft															
D2 - Left Hand single shaft															
D3 - Right Hand thru shaft															
D4 - Left Hand thru shaft															
Motor Mount (see page K-20)															
M00 - none; just shaft extension															
M99 - other															
M04 - NEMA 34 mount (E)															
M05 - NEMA 34 mount (M)															
M10 - NEMA 42 mount (E)															
M11 - NEMA 42 mount (M)															
Coupling Options (see pages K-24 & K-25)															
C000 - none															
C999 - none															
C293 to C303 - H197															
C359 to C369 - H225															
C573 to C583 - G177															
C639 to C649 - G220															
C684 to C691 - G260															
Limit & Home Switches (see pages K-21 to K-23)															
L00 - no switches															
L99 - other															
	EOT & home switches	Reed	Hall	Prox (NPN)	Prox (PNP)										
	EOT switches only	home switch only	L04	L05	L06	L07	L08	L09	L10	L11	L12	L13	L14	L15	
Encoder Options (see page K-27)															
E00 - none															
E01 - rotary (500 lines/rev)															
E02 - rotary (1000 lines/rev)															
E03 - rotary (1270 lines/rev)															
E99 - other															
<i>note: When selecting any rotary encoder option, the Drive Shaft D3 or D4 above is required.</i>															
Power-off Brakes (see page K-26)															
B00 - none															
B05 - 24 VDC															
B06 - 90 VDC															
B99 - other															
<i>note: When selecting any brake option, the Drive Shaft D3 or D4 above is required.</i>															

(E) - English Interface
(M) - Metric Interface