

614 **6** **06** - **NE** - **TB0** - **BC0** - **1** - **S005** - **M02** - **C155** - **L01R** - **E00** - **B00**

Table Series

4 - 4 bearing carriage

Carriage Length

6 - 6 inches

Travel Length (see pages F-6 to F-7)

06 - 6 to 60 inches

Screw Style

NE - no screw extension **SE** - screw extension

Tapped Mounting holes in Base (see page F-7)

TB0 - No holes **TB1** - English holes **TB2** - Metric holes

Linear Bearing Type (See page F-11)

BC0 - No Ball Chain **BC1** - With Ball Chain

Carriage Inserts (see page F-7)

1 - English mount **2** - Metric mount

Screw Options (see pages F-12 to F-17)

Rolled ball screws

S005 - .625 x .200 NPL
S006 - .625 x .200 PL
S007 - .625 x .200 NPL(T)
S008 - .625 x .200 PL(T)
S009 - .625 x 1.000 NPL
S010 - .625 x 1.000 PL
S011 - .625 x 1.000 NPL(T)
S012 - .625 x 1.000 PL(T)
S013 - .750 x .200 NPL
S014 - .750 x .200 PL
S015 - .750 x .200 NPL(T)
S016 - .750 x .200 PL(T)

Rolled ball screws

S017 - .750 x .500 NPL
S018 - .750 x .500 PL
S019 - .750 x .500 NPL(T)
S020 - .750 x .500 PL(T)

Ground ball screws

S212 - .625 x .200 PL
S213 - .625 x .500 PL
S214 - 16 x 5 PL
S215 - 16 x 16 PL

Precision ball screws

S114 - .625 x .200 NPL
S115 - .625 x .200 PL
S116 - 16 x 5 NPL
S117 - 16 x 5 PL
S118 - 16 x 10 NPL
S119 - 16 x 10 PL
S120 - 16 x 16 NPL
S121 - 16 x 16 PL
S122 - .750 x .200 NPL
S123 - .750 x .200 PL
S124 - 20 x 5 NPL
S125 - 20 x 5 PL
S128 - 20 x 20 NPL
S129 - 20 x 20 PL

S999 - other

Rolled acme screws

S300 - .625 x .100 NPL
S301 - .625 x .100 PL
S302 - .625 x .200 NPL
S303 - .625 x .200 PL

Motor Mount (see pages F-24 to F-25)

M00 - none **M02** - NEMA 23 mount (E) **M06** - NEMA 23 (RH) wrap
M01 - hand crank **M03** - NEMA 23 mount (M) **M07** - NEMA 23 (LH) wrap
M16 to M98 - see Website **M04** - NEMA 34 mount (E) **M08** - NEMA 34 (RH) wrap
M99 - other **M05** - NEMA 34 mount (M) **M09** - NEMA 34 (LH) wrap

Coupling Options (see pages F-22 to F-23)

C000 - none **C025 to C030** - C100 **C130 to C136** - H100 **C407 to C415** - G100
C999 - other **C048 to C069** - C125 **C155 to C184** - H131 **C435 to C464** - G126
C196 to C199 - H163 **C470 to C480** - G158

Limit & Home Switches (see pages F-19 to F-21 for location and specification)

L00 - no switches Mechanical Reed Hall Prox (NPN) Prox (PNP)
L99 - other EOT & home switches **L01R or L** **L04R or L** **L07R or L** **L10R or L** **L13R or L**
EOT switches only **L02R or L** **L05R or L** **L08R or L** **L11R or L** **L14R or L**
home switch only **L03R or L** **L06R or L** **L09R or L** **L12R or L** **L15R or L**

Encoder Options - SE OPTION ONLY (see page F-27)

E00 - none **E01** - rotary (500 lines/rev) **E02** - rotary (1000 lines/rev) **E03** - rotary (1270 lines/rev) **E99** - other (linear or rotary)

Power-off Brakes - SE OPTION ONLY (see page F-26)

B00 - none **B01** - 24 VDC **B02** - 90 VDC **B99** - other