


Load Capacities - ARC series

Model Number	Dynamic Load Capacity C ₅₀ (kN @ 50 km)		Static Load Capacity C ₀ (kN)		Static Moment Loads					
	Standard	with Ball Chain	Standard	with Ball Chain	M _r (Nm)		M _p (Nm)		M _y (Nm)	
					Standard	with Ball Chain	Standard	with Ball Chain	Standard	with Ball Chain
ARC 15 MS ARC 15 FS	9.7	10.7	12.1	10.8	100	85	50	45	50	45
ARC 15 MN ARC 15 FN	12.5	14.9	17.5	16.2	140	130	105	95	105	95
ARC 15 ML	16.9	19.6	26.9	24.3	215	195	235	215	235	215
ARC 20 MS ARC 20 FS	15.7	16.9	19.3	17.1	205	185	100	85	100	85
ARC 20 MN ARC 20 FN	21.5	25.6	30.0	25.7	325	275	230	200	230	200
ARC 20 ML	25.7	34.1	38.5	34.3	415	370	390	350	390	350
ARC 25 MS ARC 25 FS	22.9	24.1	27.3	24.3	350	310	160	145	160	145
ARC 25 MN ARC 25 FN	31.2	36.2	42.5	36.4	540	465	385	340	385	340
ARC 30 MS ARC 30 FS	29.3	28.7	33.1	28.9	520	455	230	205	230	205
ARC 30 MN ARC 30 FN	41.3	49.4	53.7	49.6	845	780	565	530	565	530
ARC 30 ML	49.9	65.8	70.2	66.1	1105	1040	950	900	950	900
ARC 35 MN ARC 35 FN	57.8	69.9	82.9	70.2	1700	1575	1080	1010	1080	1010
ARC 35 ML	68.9	94.4	106.5	94.7	2185	1940	1755	1575	1755	1575
ARC 45 MN	89.8	102.5	122.1	102.8	3200	2955	1910	1775	1910	1775
ARC 45 ML	112.8	159.4	169.1	159.7	4430	4185	3460	3280	3460	3280
ARC 55 MN	161.3	N.A.	186.0	N.A.	4949	N.A.	3278	N.A.	3278	N.A.
ARC 55 ML	185.2	N.A.	226.0	N.A.	6472	N.A.	5284	N.A.	5284	N.A.



N.A. - Not Available