


## Load Capacities - ARR & HRR & LRR series

Model Number	Dynamic Load Capacity C <sub>50</sub> (kN @ 50 km)		Static Load Capacity C <sub>0</sub> (kN)		Static Moment Loads						
	Standard	with Ball Chain	Standard	with Ball Chain	M <sub>r</sub> (Nm)		M <sub>p</sub> (Nm)		M <sub>y</sub> (Nm)		
					Standard	with Ball Chain	Standard	with Ball Chain	Standard	with Ball Chain	
ARR 35 MN HRR 35 MN LRR 35 MN HRR 35 FN LRR 35 FN	71.8	89.8	154	133	2742	2350	1946	1710	1946	1710	
ARR 35 ML HRR 35 ML LRR 35 ML HRR 35 FL LRR 35 FL	86.6	108.4	196	175	3525	3133	3226	2881	3226	2881	
HRR 35 MXL LRR 35 MXL HRR 35 FXL LRR 35 FXL	103.3	129.1	245	224	4439	4047	5111	4695	5111	4695	
ARR 45 MN HRR 45 MN LRR 45 MN HRR 45 FN LRR 45 FN	120.8	151.2	255	222	6350	5750	4450	4050	4450	4050	
ARR 45 ML HRR 45 ML LRR 45 ML HRR 45 FL LRR 45 FL	148.6	185.8	333	288	8450	7550	7700	6900	7700	6900	
HRR 45 MXL LRR 45 MXL HRR 45 FXL LRR 45 FXL	173.9	217.3	410	366	10500	9650	11800	10850	11800	10850	