



- \* Wide Rail Profile Bearing Blocks
- \* Alloy steel bearing, rail, and balls
- \* Equal loading in all directions
- \* 4 rows of re-circulating balls
- \* Standard & long block
- \* Standard and flanged block
- \* 2 Different accuracy ranges
- \* 3 Different preload values

- \* Standard seal option
- \* Any rail cut to specific length
- \* *Optional* - Tapped bottom rail
- \* *Optional* - Ball chain block

**ARR U 35 M N S C V1 H - 2 - 1260 - 30 - 30**

**Series Type** \_\_\_\_\_  
**ARR** - Standard Height Roller Linear Guide  
**HRR** - High Profile Roller Linear Guide

**Rail Type** \_\_\_\_\_  
 - Standard    **U** - Tapped from bottom

**Profile Size** \_\_\_\_\_  
**35** - 35 mm

**Block Width** \_\_\_\_\_  
**M** - Standard    **F** - Flanged

**Block Length** \_\_\_\_\_  
**N** - Standard    **L** - Long

**Block Seals** \_\_\_\_\_  
**S** - Standard

**Block Bearings** \_\_\_\_\_  
 - Standard    **C** - Ball Chain

**Preload Class** \_\_\_\_\_  
**V0** - Light    **V1** - Medium    **V2** - Heavy

**Accuracy Grade** \_\_\_\_\_  
**H** - High    **P** - Precision

**Number of Blocks** \_\_\_\_\_  
**2** - Number of blocks on each rail

**Rail Length** \_\_\_\_\_  
**xxxx** - Overall rail length (mm)

**Start Hole** \_\_\_\_\_  
**xx** - Distance from end (mm)

**End Hole** \_\_\_\_\_  
**xx** - Distance from end (mm)