



**DLBC** - **10** - **CR** - **L**

**Pillow Block Series** \_\_\_\_\_

- SLBC** - One LBC bushing per pillow block
- DLBC** - Two LBC bushings per pillow block
- SLBO** - One LBO bushing per pillow block
- DLBO** - Two LBO bushings per pillow block

**Nominal Diameter** \_\_\_\_\_

- 8** - 0.500 inch diameter
- 10** - 0.625 inch diameter
- 12** - 0.750 inch diameter
- 16** - 1.000 inch diameter
- 20** - 1.250 inch diameter
- 24** - 1.500 inch diameter
- 32** - 2.000 inch diameter

**Bearing Options** \_\_\_\_\_

- Standard
- CR** - Corrosion Resistance

**Bearing Lock** \_\_\_\_\_

- None
- L** - Hand Wheel Lock

### Specifications: **SLBC, SLBO, DLBC & DLBO** Pillow Blocks (self-aligning)

<p><b>Bearing Housing Type &amp; Finish</b></p> <p><b>Bearing Seals</b></p> <p><b>Corrosion Resistance</b></p> <p><b>Hand Wheel Lock</b></p>	<p>Aluminum 6061-T6 Pillow Block, Clear Anodized</p> <p>Internal Wiper Seals on Both Ends</p> <p>Electroless nickel plated load bushing plates and stainless steel recirculating balls</p> <p>Optional Aluminum Shaft Clamping Block</p>																
<p><b>Operating Temperature</b></p> <p><b>Maximum Speed</b></p> <p><b>Matching Shaft</b></p>	<p>0° F to + 185° F</p> <p>9.8 ft/second (3m/sec)</p> <p>Class L (<b>SL</b> series), hardened &amp; ground shafting</p>																
<p><b>Diameter Tolerance</b></p>	<table border="1"> <thead> <tr> <th>Nominal Shaft Diameter (inches)</th> <th>Shaft Diameter Tolerance (inches)</th> </tr> </thead> <tbody> <tr> <td>0.500</td> <td>.4995 / .4990</td> </tr> <tr> <td>0.625</td> <td>.6245 / .6240</td> </tr> <tr> <td>0.750</td> <td>.7495 / .7490</td> </tr> <tr> <td>1.000</td> <td>.9995 / .9990</td> </tr> <tr> <td>1.250</td> <td>1.2495 / 1.2490</td> </tr> <tr> <td>1.500</td> <td>1.4994 / 1.4989</td> </tr> <tr> <td>2.000</td> <td>1.9994 / 1.9987</td> </tr> </tbody> </table>	Nominal Shaft Diameter (inches)	Shaft Diameter Tolerance (inches)	0.500	.4995 / .4990	0.625	.6245 / .6240	0.750	.7495 / .7490	1.000	.9995 / .9990	1.250	1.2495 / 1.2490	1.500	1.4994 / 1.4989	2.000	1.9994 / 1.9987
Nominal Shaft Diameter (inches)	Shaft Diameter Tolerance (inches)																
0.500	.4995 / .4990																
0.625	.6245 / .6240																
0.750	.7495 / .7490																
1.000	.9995 / .9990																
1.250	1.2495 / 1.2490																
1.500	1.4994 / 1.4989																
2.000	1.9994 / 1.9987																