

Support Housing Dimensions

Simple

inches (mm)

(4) .343 (8,71) Dia.Thru Holes

(4) 8-32 x .37 (9,39) Deep on 1.750 (44,45) BC

1.250 (31,75)

2.500 (63,50)

1.750 (44,45)

.625 (15,87)

2.000 (50,80)

1.625 (41,27)

3.250 (82,55)

.375 (9,52)

Weight (each)
Aluminum: 0.4 lbs (0,18 kg)
Steel: 1.1 lbs (0,50 kg)

303 Woodruff Keyways on Both Extensions

Drive End

non-Drive End

.313 (7,95)

(2) .343 (8,71) Dia. Thru Holes, .504 (12,8) Dia. C' Bored x .57 (14,47) Deep

.625 (15,87)

Fixed

(4) .343 (8,71) Dia.Thru Holes

(4) 8-32 x .37 (9,39) Deep on 1.750 (44,45) BC

1.250 (31,75)

2.500 (63,50)

1.750 (44,45)

.625 (15,87)

2.000 (50,80)

1.625 (41,27)

3.250 (82,55)

.375 (9,52)

.250 (6,35)

Weight (each)
Aluminum: 0.9 lbs (0,41 kg)
Steel: 2.6 lbs (1,18 kg)

303 Woodruff Keyways on Both Extensions

(4) .343 (8,71) Dia. Thru Holes, .504 (12,8) Dia. C' Bored x .57 (14,47) Deep

(2) 10-32 x .43 (10,92) Deep, both sides

1.125 (28,57)

.750 (19,05)

.375 (9,52)

.688 (17,47)

.125 (3,17)

1.625 (41,27)

Rigid

(4) .343 (8,71) Dia.Thru Holes

(4) 8-32 x .37 (9,39) Deep on 1.750 (44,45) BC

1.250 (31,75)

2.500 (63,50)

1.750 (44,45)

.625 (15,87)

2.000 (50,80)

1.625 (41,27)

3.250 (82,55)

.375 (9,52)

.250 (6,35)

Weight (each)
Aluminum: 1.3 lbs (0,59 kg)
Steel: 3.8 lbs (1,72 kg)

303 Woodruff Keyways on Both Extensions

(4) .343 (8,71) Dia. Thru Holes, .504 (12,8) Dia. C' Bored x .57 (14,47) Deep

(2) 10-32 x .43 (10,92) Deep, both sides

1.125 (28,57)

1.375 (34,92)

.375 (9,52)

.688 (17,47)

.125 (3,17)

2.250 (57,15)

NEMA 23 Motor Mount

Material: Aluminum
Weight: 0.9 lbs (0,41 kg)

(4) Holes on 2.625 (66,67) BC Dia. English (M02): #10-24 thd. Metric (M03): M5 thd.

1.502 (38,15) Pilot Dia. TYP

2.340 (59,44)

2.562 (65,07)

.313 (7,95)

1.437 (36,50)

2.250 (57,15)

1.125 (28,57)

(2) .221 (5,61) Dia.Thru Holes, .344 (8,73) Dia. C' Bored x .125 (3,17) Deep, both sides

3.250 (82,55)

NEMA 34 Motor Mount

Material: Aluminum
Weight: 1.4 lbs (0,64 kg)

(4) Holes on 3.875 (98,42) BC Dia. English (M04): #10-24 thd. Metric (M05): M5 thd.

2.877 (73,07) Pilot Dia. TYP

.063 (1,60)

2.340 (59,44)

.500 (12,70)

2.562 (65,07)

.313 (7,95)

1.937 (49,20)

3.375 (85,72)

1.688 (42,88)

.438 (11,13)

(2) .221 (5,61) Dia.Thru Holes, .344 (8,73) Dia. C' Bored x .125 (3,17) Deep, both sides

3.375 (85,72)

Specifications subject to change without notice