

	RS	150	025	-	S1	A	-	N1	-	W0	-	F1	-	M04	-	C223	-	E00	-	B00	-	Lxxx.xxx
Rolled Screw																						
Screw Diameter																						
150 - 1.500 inch																						
Screw Lead																						
025 - 0.250 inch																						
050 - 0.500 inch																						
100 - 1.000 inch																						
200 - 2.000 inch																						
Support Configurations																						
S1 - Simple - Simple																						
S2 - Fixed (LT) - Simple																						
S3 - Fixed (HT) - Simple																						
S4 - Rigid - Simple																						
S5 - Rigid - Rigid																						
S9 - other																						
Support Material																						
- Steel																						
A - Aluminum																						
Nut Type																						
N1 - NPL ball nut (RFT)																						
N2 - NPL ball nut (LFT)																						
N3 - PL ball nut (RFT)																						
N4 - PL ball nut (LFT)																						
N9 - other																						
Nut Wipers																						
W0 - none																						
W1 - Wipers on Ball Nut																						
Nut Flange Type																						
F0 - none																						
F1 - Round flange																						
F2 - Vertical bracket (E)																						
F3 - Vertical bracket (M)																						
F4 - L bracket (E)																						
F5 - L bracket (M)																						
F9 - other																						
Motor Mount																						
M00 - none																						
M04 - NEMA 34 mount (E)																						
M05 - NEMA 34 mount (M)																						
M08 - NEMA 34 (RH) wrap																						
M09 - NEMA 34 (LH) wrap																						
M10 - NEMA 42 mount (E)																						
M11 - NEMA 42 mount (M)																						
M12 - NEMA 42 (RH) wrap																						
M13 - NEMA 42 (LH) wrap																						
M99 - other																						
Coupling Type																						
C000 - none																						
C999 - other																						
C223 to C233 - H163																						
C281 to C291 - H197																						
C337 to C347 - H225																						
C503 to C513 - G158																						
C561 to C571 - G177																						
C617 to C627 - G220																						
Rotary Encoder																						
E00 - none																						
E99 - other																						
E27 - 500 lines/rev																						
E28 - 1000 lines/rev																						
E29 - 1270 lines/rev																						
Power-off Brake																						
B00 - none																						
B99 - other																						
B24 - 24 VDC																						
B25 - 90 VDC																						
Thread Length																						
Lxxx.xxx - screw thread length (inches)																						

(E) - English Interface	(M) - Metric Interface
(LFT) - Left Facing Thread	(NPL) - Non Preloaded
(LH) - Left Hand	(PL) - Preloaded
(LT) - Low Thrust	(RFT) - Right Facing Thread
(HT) - High Thrust	(RH) - Right Hand